

www.anatol.com

SOLUTIONS mini

High Efficiency Electric Dryer

Designed For Practicality

- Compact, space-saving design fits shops of all sizes
- Ceramic heating elements provide even heat d istribution and reduce future maintenance costs
- Overall length from 5ft to 6.5ft

Available in configurations of:

- 24" wide belt up to 48" wide belt
- 2.5ft heat chamber up to 4ft heat chamber





STANDARD FEATURES



Design and Construction

- Industrial grade AC motor
- Heavy-duty construction
- High efficiency thermal insulation prevents heat from migrating into the workplace

444

Control Center

- Precise and easy-to-use digital temperature controls
- Adjustable belt speed to accommodate a variety of ink and substrate curing requirements

€

Heating Elements

- Ceramic heating elements heat up quickly and distribute heat evenly and efficiently
- 2" x 8" elements arranged in a grid of 6-15 total elements, depending on dryer configuration (see specification table)

©

Conveyor System

- Industrial grade conveyor rollers
- Adjustable infeed/outfeed openings
- Teflon-coated fiberglass belt with speed control
- Belt tracking ensures the belt is precisely aligned at all times

Options

- Custom dryer size (length and width)
- Infeed/outfeed extension(s) per customer requirements
- Outfeed cooling fan to boost ink cooling when substrate exits the heat chamber
- Single-phase wiring to accommodate facilities with single phase electricity



| Model # | Belt Width | Heat Chamber | Overall Length | Standard Infeed/Outfeed Length | Wattage | Ceramic Elements | Electrical Requirements | Model # |
|-----------|---------------|-----------------|-------------------|--------------------------------------|---------|---------------------|---|-----------|
| SEDM242.5 | 24" 61cm | 2′6″ 75 cm | 5′0″ 150 cm | 1′3″/1′3″ 38cm/38cm | 3900 | 6 | 1 Ph, 208-230 V, 3.9 kW, 19A, 50/60Hz | SEDM242.5 |
| SEDM2404 | 24" 61cm | 4′0″ 120 cm | 6'6" 195 cm | 1′3″/1′3″ 38cm/38cm | 5850 | 9 | 1 Ph, 208-230 V, 5.85 kW, 29A, 50/60Hz | SEDM2404 |
| SEDM362.5 | 36" 92cm | 2'6" 75 cm | 5′0″ 150 cm | 1'3"/1'3" 38cm/38cm | 5850 | 9 | 1 Ph, 208-230 V, 5.85 kW, 29A, 50/60 Hz | SEDM362.5 |
| SEDM482.5 | 48" 122cm | 2'6" 75 cm | 5′0″ 150 cm | 1′3″/1′3″ 38cm/38cm | 9750 | 15 | 1 Ph, 208-230 V, 9.75 kW, 47A, 50/60 Hz | SEDM482.5 |

Two-Year Limited Warranty

Every effort has been made to ensure the accuracy of the promotional information included in this brochure. Specifications are subject to change. Anatol Equipment Manufacturing Co. and its subsidiaries, if any, expressly disclaim any liability for damages, consequential or incidental, resulting from the purchase, transportation, installation, or use of any products based upon information contained within this brochure. Any rights or remedies are limited solely to those provided in writing by Anatol Equipment Manufacturing Co. at the time of sale