

# SOLUTIONS

## High Efficiency Electric Dryer

### Superior Technology

- Up to 9 programmable job settings
- Automatic cool-down mode
- Intuitive touchscreen operating system

### Designed For Practicality

- Ceramic heating elements reduce future maintenance costs

### Available in 7 different configurations:

- Models available from 24" belt width/4' heat chamber up to 60" belt width/9'6" heat chamber



## STANDARD FEATURES



### Design and Construction

- Industrial grade AC motor
- Heavy-duty multiple section construction
- Double wall construction with galvanized interior
- High efficiency thermal insulation prevents heat from migrating into the workplace
- Air-cooled control cabinet



### Conveyor System

- Teflon-coated fiberglass belt with digital speed control
- Industrial grade conveyor rollers
- Adjustable infeed/outfeed openings



### Control Center

- User-friendly and intuitive touchscreen control system
- Solid-state variable belt speed controller
- Programmable temperature controller
- Work Schedule mode allows you to program the dryer to automatically start up and shut down at specified times on given days of the week
- View your daily power consumption and total power consumption to help you determine your energy costs and identify potential electrical issues



### Heat Chamber

- Ceramic heating elements – 9-48 total elements, depending on dryer configuration
- Adjustable heat panels (raise and lower)



### Options

- Custom dryer sizes (length and width)
- Infeed/outfeed extension(s) per customer requirements
- Outfeed cooling fan to boost ink cooling when substrate exits the heat chamber
- Single-phase wiring to accommodate facilities with single phase electricity

MODEL	BELT WIDTH	HEAT CHAMBER	OVERALL LENGTH	STANDARD INFEED/OUTFEED	WATTAGE	PIECES PER HR.	CERAMIC ELEMENTS
SED-2404A-5850	24"	4'0"	9'0"	5'0"	5850 W	120-200	9
SED-2404A-7800	24"	4'0"	9'0"	5'0"	7800 W	150-250	12
SED-3606A-15600	36"	6'0"	11'0"	5'0"	15600 W	400-600	24
SED-3610A-23400	36"	9'6"	19'6"	10'0"	23400 W	550-800	36
SED-4810A-26000	48"	9'6"	19'6"	10'0"	26000 W	700-950	40
SED-6010A-31200	60"	9'6"	19'6"	10'0"	31200 W	900-1200	48

### Two-Year Limited Warranty

Every effort has been made to ensure the accuracy of the promotional information included in this brochure. Specifications are subject to change. Anatol Equipment Manufacturing Co. and its subsidiaries, if any, expressly disclaim any liability for damages, consequential or incidental, resulting from the purchase, transportation, installation, or use of any products based on information contained within this brochure. Any rights or remedies are limited solely to those provided in writing by Anatol Equipment Manufacturing CO. at the time of sale.